

## DAFTAR PUSTAKA

- Ahmad, A., Glasgow. C., and Weat. T.A (1995). “Sol-gel processing of NASICON thin-film precursor”, *Solid State Ionic.* Vol 76, 143-154.
- Brinker, C. J and Scherer, G. W. (1990). Sol-Gel Science – the physics and chemistry of Sol-Gel processing. New York, Academic press.
- Bhonke. O., Ronchetti, S., Mazza, D. (1999). Conductvity Measurements on NASICON and NASICON-Modified Materials. *Solid State Ionic.* Vol 122, 127-136.
- Dewi, R. (2007). Sintesis dan Karakterisasi Material Konduktor Ionik Komponen Gas Nox Melalui Metode Sol-Gel Anorganik. Universitas pendidikan Indonesia.
- Gelling, P. J., dan Boumeester H. J. (1997). *The CRC HandBook of Solid State Electrochemistry.* Boca Raton: CRC Press
- Goodenought, J.B.,Hong, H.Y-P.,and Kalafas, J.A. (1976). “fast Na<sup>+</sup> ion transport in skeleton structures”. *Materil research bulletin.* Vol 11, 203-220.
- Hong, H.Y-P. (1976). “Cyristal Structure and Cyristal Chemistry in the system Na<sub>1+x</sub>Si<sub>x</sub>P<sub>3-x</sub>O<sub>12”</sub>. *Materil research bulletin.* Vol 11, 173-182.
- Kida, T. Shimanoe, K. Miura, N. and Yamazoe, N. (2001). Stability of NASICON-Based CO<sub>2</sub> sensor under humid conditions at low temperature. *Sensor and actuators B.* Vol 75, 179-187.

Kumar, P. P Yashonath, S. (2006). *Ionic Conductor In Solid State*. J Chem Sci. Vol 118, 135, 134.

Kris Tri Basuki, (tanpa tahun). Penurunan Konsentrasi CO dan NO<sub>2</sub> pada Emisi Gas Buang dengan menggunakan Media Penyisipan TiO<sub>2</sub> Lokal pada Karbon Aktif. PTAPB-BATAN Yogyakarta.

Luisa Di Vona, M. Liccoccia, S. Montanaro, L. and Traversa, E. (1999). Sol Gel Synthesis of NASICON: 1D and 2D NMR-Investigation. *Chem. Mater.* Vol 11, 1336 1341.

Liccoccia, S. Luisa Di Vona, M. Traversa, E. and Montanaro, L. (1999). NMR study of sol-gel processed NASICON. Jounal of European Ceramic Society. Vol 19, 925-929.

Lee, J. S., Lee, J. H and Hong, S-H. (2003) Nasicon Based Amperometric CO<sub>2</sub> sensorusing Na<sub>2</sub>CO<sub>3</sub>-CaCO<sub>3</sub> auxiliary phase. *Sensor and actuator B*. Vol 96, 663-668.

Min, B-K. Choi, S-D. (2003). SO<sub>2</sub>-sensing characteriscs of NASICON sensor with Na<sub>2</sub>SO<sub>4</sub>-BaSO<sub>4</sub> auxiliary electrolytes. *Sensors and actuators B*. Vol 93, 209-213.

Miura, N., Lio, M., Lu, G and Yamazoe N. (1996). Solid-state amperometric NO<sub>2</sub> sensor using a sodium ion conductor. *Sensors and actuators B*. Vol 35-36, 124-129.

Miura, N., Yao, S., Shimizu Y and Yamazoe N. (1993). Development of high-performance solid electrolyte sensors for NO and NO<sub>2</sub>. *Sensors and actuators B*. Vol 13-14, 387-390.

- Miyachi, Y., Sakai, G., Shimanoe, K. and Yamazoe, N. (2003). Fabrication of CO<sub>2</sub> sensor using NASICON thick film. *Sensor and actuator B*. Vol 93, 250-256.
- Mouazer, R., Elmarakki, Y., Persin. M., Cretin, M., Sarrazin, J., and Larbot. A. (2003) "Role of citrate and tartaric ligands for the stabilization of NASICON sols. Application to membrane preparation". *Colloids and surfaces A: Phisicochem. Eng. Aspects*. Vol 216, 261-273.
- Obata, K. Kumazawa, S. Matsushima, S. Shimanoe, N. and Yamazoe. (2005). NASICON-based potentiometric CO<sub>2</sub> sensor combined with new materials operativeatroom temperature. *Sensors and Actuators B*. Vol 108, 352–358.
- Obata, K., Kumazawa, S., Matsushima, S., Shimanoe, N., N. and Yamazoe. (2005). NASICON-Based potentiometric CO<sub>2</sub> sensor combined with new materials operativeatroom temperature. *Sensor and actuator B*. Vol 108, 352-358.
- Ono, M., Shimanoe, K., Miura, N., (2000). "Amperometric sensor based on NASICON and NO oxidation catalysts for detection of total NOx in atmospheric inverontment". *Solid state ionic*. Vol 136-137, 583-588.
- Qiu, F., Zhu, Q., Yang, X., Quan, Y. and BaokunXu. (2004). Preparation of planar CO<sub>2</sub> sensor based on solid-electrolite NASICON synthesised by sol-gel process. *Material chemistry and physics*. Vol 83, 193-198.
- Qiu, F., Zhu, Q., Yang, X., Quan, Y. and Sun, L. (2003). Investigation of CO<sub>2</sub> sensor based of NASICON synthesized by a new sol-gel process. *Sensor and actuator B*. Vol 93, 237-242.

Rao, C.N.R and J. Gopalakrishnan. (1997). *New Directions in Solid State Chemistry*, pp. 409-416, Cambridge.

Restiana, N.,(2008). Pengaruh kestabilan sol pada karakter material ionik komponen sensor gas NOx hasil preparasi melalui metode sol-gel. Universitas pendidikan indonesia.

Romer, E. (2001). *Amperometric NO<sub>x</sub>-sensor for Combustion Exhaust Gas Control*. University of Twente. Twente University Press.

Sadaoka, Y. (2007). NASICON based CO<sub>2</sub> gas sensorwith an auxiliary electrode composed of LiCO<sub>3</sub>-metal oxide mixtures. *Sensors and Actuators B*. Vol 121, 194–199.

Shimizu, Y. and Ushijima, T. (2000). “Sol-gel processing of NASICON thin film using aqueous complex precursor”. *Solid state ionic*. Vol 132, 143-148.

Szabo. N. et al. (2003) “Cerami-based chemical sensor, probes and field-test in auto mobile enginis”. *Journal of material science*. Vol 38, 4239-4245.

Zang, S., Quan, B., Zhao, B., Ile, Y., Chen, W. (2003). Pereparation and cracterization of NASICON with a new sol-gel process. *Material latters*. Vol 58, 226-229.

ZHU Dong-mei., LUO Fa., XIE Zhang-long., ZHOU Wan-cheng. (2007) *State Key Laboratory of Solidification Processing*. Northwestern Polytechnical University, Xi'an 710072, China

V. M. Aroutiounian (2007). Semiconductor NO<sub>x</sub> Sensors. *Department of Physics of Semiconductors and Microelectronics at Yerevan State University 0025, 1, A. Manoukyan, Yerevan, Armenia*.